

## **ENDOORS Srl.**

Via Argine Maestro del Po, 9 43010 Polesine Parmense / PR ITALY

VAT IT02561400348

info@en-doors.com - commercial and sales office info@endoors.it - production, administration, shipping Tel. 0524 936538

Tel. 0524 936538 Fax 0524 936544 www.endoors.it

BRD 212-Rev. 1/11

## □ QUOTATION □ ORDER **BIG ROTATION DOOR FIRE FIXING® REI 120 2 LEAVES** Customer Date \_\_\_\_\_ Page n° ..... of pages ..... Item code INSIDE WALL OPENING MOUNTING LT+20 NOTES: Wall reveal to be SIDE LT built after door - Elements providing fire RAWLPLUGS 10 installation at LN compartimentation. Do not customer's RIGHT expenses. use inappropriately. LEFT HT-10 (Min. 800 mm) -— LNm (Min. 860 mm) Fill with mortar of HT+10 - Mounting to be carried out by UPPER SIDE specialized personnel only. HN 20 OUTSIDE WALL OPENING OR WALL EMBEDDED MOUNTING \* нт Do not install in places DOOR CLOSER 70-☐ CONTINUOUS ANGLE subject to direct air flow. 70 THROUGH RAWLPLUGS Mount only on flat plumb 134 \_134 vertical structures or RH LH UPPER compartments suitable to B00STER 70~ bear the heavy radial load. Dangerous closing during ☐ FRONT RAWLPLUGS HANDLE 70rotation caused by "boom RH LH UPPER Precautions during use and Leaves can be manufactured with risk analysis are to be defined without joints according to dimensions Leaves with different dimensions may ■ BRACKETS AND/OR by the customer. ANGLES THROUGH be esthetically different. - For special requirements, Modules subject to deformation **RAWLPLUGS** please indicate available RH LH UPPER All pictures are illustrative and out of scale spaces and contact our All dimensions are expressed in millimetres. The type approval number will be assigned when order or production is confirmed. Technical Office \* The basic model includes side fixing through rawlplugs. \_\_\_\_\_ mm \_\_\_\_\_ Price Net price Amount % € € ..... mm **x HN** □ DIFFERENT LEAVES ☐ LEFT RIGH **OPENING PULL** (main leaf) BRD FIRE FIXING® REI 120 includes the RAL 7035 prime coat finishing. PRESELECTOR (CLOSING REGULATOR) DOOR CLOSER □ 80N 160N BOOSTER (Coil spring) max opening 120° ELECTROMAGNET 24 V d.c. CC 1400N NC RELEASE BUTTON 1 Firux® I.S.D. supplier + 2 THERMAL DETECTORS Have to be installed on doors without any centralized monitoring system (choice to be preferred). PANIC BAR (handle center at 1050 mm from ffl) ☐ SLASH ☐ TWIST ☐ STAINLESS STEEL SLASH ☐ STAINLESS STEEL TWIST CONTINUOUS ANGLE FOR OUTSIDE WALL OPENING MOUNTING THROUGH RAWLPLUGS mm BRACKETS FOR INSIDE WALL OPENING MOUNTING THROUGH BRACKETS SPECIAL GAP COVER PROFILE mm SUPPLEMENT IN CASE OF DIFFERENT LEAVES ONE WAY METAL PACKAGING IF LT/HT > 2600 mm or LNm (or LNf) > 2400 mm RAL OVEN-HARDENED SATIN FINISH \_\_\_ If ${\rm HT} > 2650~{\rm mm}$ or LNm (or LNf) > 2450 only off line RAL 7035 prime coat available. TOTAL € (VAT excluded)

General and particular sales conditions including delivery times are given in annex form of offer or order confirmation. Excluding transportation, unloading from truck or container, installation, destination taxes and charges. Packing included. Every single order to become economically and technically engaging must be confirmed in writing by Endoors srl. since before the formalization of the order the product or documentation may have changed. Incomplete forms to become effective must be completed both for offers and orders.

Special notes	Seal and signa	ature for acceptance and confirmation of order